



**Rotary Union**



# Soniq Linkable Retail Linear

30/40/50W 4ft

## Applications:

Residential and Commercial Applications.

- High Power Factor >0.9 BOKE LED Driver with a 2.5kV Surge Protection offering a robust luminaire with a 5 year warranty.
- Pure Aluminum housing coupled with a PC diffuser, designed to ensure maximum comfort for customers when used in retail applications.
- Linkable up to 60m or 50 x 4ft SoniQ Linears. Ideal for long isles where continuous lighting is a requirement.
- L80B20 @ 50 000hrs ensuring minimal lumen decay throughout the 5 year warranty period.
- Available in either 60°/90°(standard) & 120° beam angles, allowing for an extremely versatile luminaire to suit most applications.
- Available in 3CCT (3000K/4000K/6000K) Controlled via the luminaires dipswitch for a quick and easy CCT transition.
- High CRI>80 making the SoniQ the ideal Retail & Commercial LED Solution.

## Product Performance


<b>Wattage</b>	30/40/50W
<b>Colour Temperature &amp; Stock</b>	3CCT Black - <b>LL705</b>   3CCT White - <b>LL706</b>
<b>Operating Temperature</b>	-25~40°C
<b>Life Span/ LB Rating</b>	L80B20@50000H
<b>IP Rating</b>	IP20
<b>LED Driver Brand</b>	PioLED High Spec Driver
<b>Beam Angle</b>	90°
<b>Impact Protection Grade</b>	IK08
<b>Input Voltage</b>	AC180-277V
<b>Surge Protection</b>	2.5kV
<b>Power Factor</b>	0.9
<b>CRI</b>	>80
<b>Lumen Output</b>	30W= 4 500lm   40W= 6 000lm 50W= 7 500lm
<b>Lumen Efficiency</b>	150lm/W
<b>LED Chips</b>	Epistar 2835
<b>LED Chips Qty</b>	288
<b>Dimmable</b>	No
<b>Dimmable Range</b>	-

**Notes** 4 Hanging kits included | Max. link 2200W or 55meter

## Physical Characteristics

<b>Weight (kg)</b>	1,45
<b>Housing Material</b>	White/Black AL+SS Clips
<b>Product Dimensions (mm)</b>	1158*74*52
<b>Cable Length</b>	1.2m
<b>Mounting Option</b>	Surface/Suspension
<b>Bracket Material</b>	-


## Luminous Intensity Distribution Diagram



## Packaging



## Dimension Drawing



## Technical Parameters

<b>Input Current</b>	360mA
<b>Output Voltage</b>	72
<b>Flicker Free (Y/N)</b>	Yes
<b>Humidity</b>	40%~80%
<b>Frequency</b>	50-60hz
<b>In Rush Current</b>	16.5A
<b>Output Current</b>	0.75A
<b>THD</b>	<20%
<b>TA &amp; TC</b>	TA= -20~45 °C/TC=65°C
<b>IES (Yes or No)</b>	Yes

## Regulatory Qualifications

<b>Class Rating</b>	Class I
<b>Energy Efficiency</b>	A
<b>Certification</b>	CE, EMC, IEC60958

## Accessories

### Optional accessories


- SONIQ 60D lens x 1 (4ft needs 4) - **LL705a**
- SONIQ 1.2m 120D Opal Cover - **LL705b**
- SONIQ Rotary Union - Black - **LL705c**
- SONIQ Batwing LR40 30°/30° lens SQ x 1 (4ft needs 4) - **LL705d**
- SONIQ 3CCT 4Gr Linkable L Shape Linear Light 90D - **LL710**
- SONIQ 40CM Black bracket with 3M hanging Cable - **LL705f**
- SONIQ 30CM Black Honeycomb Cover - **LL705g**
- SONIQ L Shape Opal Cover - **LL705h**
- Suspended Ceiling Clips White (Pair) - **R114**

## Packaging info

<b>Storage Temp</b>	-40~+60°C
<b>Carton Size (mm)</b>	1260*260*255
<b>QTY/CTN</b>	12
<b>Net Weight</b>	17,5
<b>Gross Weight</b>	19



# Soniq Accessories



## Applications:

Residential and Commercial Applications.

- High Power Factor >0.9 BOKE LED Driver with a 2.5kV Surge Protection offering a robust luminaire with a 5 year warranty.

- Pure Aluminum housing coupled with a PC diffuser, designed to ensure maximum comfort for customers when used in retail applications.


- Linkable up to 60m or 50 x 4ft SoniQ Linears. Ideal for long isles where continuous lighting is a requirement.

- L80B20 @ 50 000hrs ensuring minimal lumen decay throughout the 5 year warranty period.

- Available in either 60°/90°(standard) & 120° beam angles, allowing for an extremely versatile luminaire to suit most applications.

- Available in 3CCT (3000K/4000K/6000K) Controlled via the luminaires dipswitch for a quick and easy CCT transition.


- High CRI>80 making the SoniQ the ideal Retail & Commercial LED Solution.




Rotary Union



Suspended Ceiling Clips White (Pair)



Honeycomb Lens



L Shape Linear

40cm Black Bracket with 3M hanging Cable

