



Rotary Union



Soniq Linkable Retail Linear

10W

Applications:

Residential and Commercial Applications.

- High Power Factor >0.9 BOKE LED Driver with a 2.5kV Surge Protection offering a robust luminaire with a 5 year warranty.
- Pure Aluminum housing coupled with a PC diffuser, designed to ensure maximum comfort for customers when used in retail applications.
- Linkable up to 60m or 50 x 4ft SoniQ Linears. Ideal for long isles where continuous lighting is a requirement.
- L80B20 @ 50 000hrs ensuring minimal lumen decay throughout the 5 year warranty period.
- Available in either 60°/90°(standard) & 120° beam angles, allowing for an extremely versatile luminaire to suit most applications.
- Available in 3CCT (3000K/4000K/6000K) Controlled via the luminaires dipswitch for a quick and easy CCT transition.
- High CRI>80 making the SoniQ the ideal Retail & Commercial LED Solution.


Product Performance

Wattage	10W
Colour Temperature & Stock	3CCT Black - LL707 3CCT White - LL708
Operating Temperature	-25~40°C
Life Span/ LB Rating	L80B20@50000H
IP Rating	IP20
LED Driver Brand	PioLED High Spec Driver
Beam Angle	90°
Impact Protection Grade	IK08
Input Voltage	AC180-277V
Surge Protection	2.5kV
Power Factor	0.9
CRI	>80
Lumen Output	1 500
Lumen Efficiency	150lm/W
LED Chips	Epistar 2835
LED Chips Qty	180
Dimmable	No
Dimmable Range	-
Notes	2 Hanging kits included Max. link 2200W or 55meter


Physical Characteristics

Weight (kg)	0.712
Housing Material	Pure Aluminium
Product Dimensions (mm)	300*74*52
Cable Length	0.3m
Mounting Option	Surface/Suspension
Bracket Material	-

Packaging



Dimension Drawing



Technical Parameters

Input Current	45mA
Output Voltage	45
Flicker Free (Y/N)	Yes
Humidity	40%~80%
Frequency	50-60hz
In Rush Current	10A
Output Current	0.2A
THD	<20%
TA & TC	TA= -20~45 °C/TC=65°C
IES (Yes or No)	Yes

Regulatory Qualifications

Class Rating	Class I
Energy Efficiency	A
Certification	CE, EMC, IEC60958

Accessories

Optional accessories


SONIQ 60D lens x 1 (1ft needs 1) - **LL705a**
 SONIQ 1.2m 120D Opal Cover - **LL705b**
 SONIQ Rotary Union - Black - **LL705c**
 SONIQ Batwing LR40 30°/30° lens SQ x 1 (1ft needs 1) - **LL705d**
 SONIQ 3CCT 4Gr Linkable L Shape Linear Light 90D - **LL710**
 SONIQ 40CM Black bracket with 3M hanging Cable - **LL705f**
 SONIQ 30CM Black Honeycomb Cover - **LL705g**
 SONIQ L Shape Opal Cover - **LL705h**
 Suspended Ceiling Clips White (Pair) - **R114**

Packaging info

Storage Temp	-40~+60°C
Carton Size (mm)	790*340*310
QTY/CTN	40
Net Weight	28,5
Gross Weight	34



Soniq Accessories



Applications:

Residential and Commercial Applications.

- High Power Factor >0.9 BOKE LED Driver with a 2.5kV Surge Protection offering a robust luminaire with a 5 year warranty.

- Pure Aluminum housing coupled with a PC diffuser, designed to ensure maximum comfort for customers when used in retail applications.


- Linkable up to 60m or 50 x 4ft SoniQ Linears. Ideal for long isles where continuous lighting is a requirement.

- L80B20 @ 50 000hrs ensuring minimal lumen decay throughout the 5 year warranty period.

- Available in either 60°/90°(standard) & 120° beam angles, allowing for an extremely versatile luminaire to suit most applications.

- Available in 3CCT (3000K/4000K/6000K) Controlled via the luminaires dipswitch for a quick and easy CCT transition.


- High CRI>80 making the SoniQ the ideal Retail & Commercial LED Solution.




Rotary Union



Suspended Ceiling Clips White (Pair)



Honeycomb Lens



L Shape Linear

40cm Black Bracket with 3M hanging Cable

