



LED 12n24V CV 2 Sec Driver

100W

PioLED Lighting (Pty) Ltd
031 701 5746
info@pioledlighting.africa

*AUTO SENSE 12V/24V

Switch OFF AC power for ≥ 5 sec before changing LED strip.

Failure to do so may damage the 12V LED strip

****Flick switch on/off within 2 seconds to drop brightness****

Product Performance

Wattage	100W (8.5 Amp for 12V) (4.2Amp for 24V)
Colour Temperature & Stock Code	PS018
Operating Temperature	-30 ~ 45°C
IP Rating	IP20
Input Voltage	AC 176-264V
Surge Protection	L,N: 1KV L,N-PE: 2KV
Dimmable	Yes

Physical Characteristics

Weight (g)	210
Housing Material	Aluminium
Product Dimensions (mm)	H 24 x L 145 x W 48

Technical Parameters

Input Current	0.88A/230V AC
Output Voltage	12V DC or 24V DC
Frequency	50/60Hz
Output Current	Max 8.5A or 4.2A
IES (Yes or No)	No

Regulatory Qualifications

Energy Efficiency	A
Certification	IEC, CE, RoHS

Packaging info

QTY/CTN	90
Net Weight	21.4KG
Gross Weight	22KG

E&OE

PioLED Lighting (Pty) Ltd | 031 701 5746 | info@pioledlighting.africa

www.pioledlighting.co.za